



**packaging**

fast-setting concrete mix



Material Safety Data Sheet

**Health = 1**

**Flammability = 0**

**Reactivity = 0**

ASH GROVE PACKAGING GROUP  
10809 Executive Center Drive, Ste. 321  
Little Rock, AR 72211  
Phone: (888) 289.1117  
Fax: (501) 224.3882  
[www.ashgrovepkg.com](http://www.ashgrovepkg.com)

**Section I. Product Identification**

Trade Name: Ash Grove® Fast-Setting Concrete Mix  
Synonyms: Dry Powder, Portland Mortar  
Manufacturer and/or Supplier: Materials Packaging Company  
Address: 10809 Executive Center Drive  
Manufacturer and Emergency Telephone: (888) 289 -1117  
Effective Date: October 9, 2009

**Section II. Hazardous Ingredients**

Description	CAS#	TLV	PEL	Vapor Pres.
Portland Cement	65997-15-1	5mg/m3	5mg/mg	NA
Crystalline Silica	14808-60-7	10mg/m	.05mg/m3	NA
Proprietary Additives	Non-hazardous	5mg/m3	NE	NA

**Section III. Physical Data**

Boiling Point: NA  
Vapor Pressure (mmHg.): NA  
Vapor Density (Air = 1): NA  
Solubility in Water: Slight  
Appearance/Odor: Gravel and sanded powder; No odor  
Specific Gravity (Water = 1): 2.5-3.15  
% Volatile by Volume (%): 0  
Evaporation Rate: NA



packaging

fast-setting concrete (cont.)

#### Section IV. Fire & Explosion Hazard Data

Flash Point:	Non-Flammable
Flammable Limits – UEL (%):	NA
- LEL (%):	NA
Extinguishing Media:	NA
Special Firefighting:	None required
Unusual Fire and Explosion Hazards:	None

#### Section V. Health Hazard Data

Threshold Limit Value:	Respirable dust – TLV 10mg/m3
Effects of Overexposure:	Excessive exposure by inhalation over an extended period of time may result in the development of pulmonary diseases including pneumoconiosis and silicosis. Skin and eye irritant. Can cause alkali burns and dermatitis.
Emergency First Aid:	
Skin:	Wash thoroughly with soap and water.
Eyes:	Flush thoroughly with water for 15 minutes. Consult physician if irritation persists.
Inhalation:	Remove from exposure.
Ingestion:	Give large doses of water to dilute.

#### Section VI. Reactivity Data

Stability:	Stable
Stability Conditions to Avoid:	Strong acids may cause violent, exothermic reaction.
Materials to Avoid:	NA.
Hazardous Decomposition Products:	NA
Hazardous Polymerization:	Will not occur

#### Section VII. Spill or Leak Procedures

Spill or Leak Procedures:	Spills or leaks can be swept or vacuumed. Sweeping compound or sand may be mixed with material to help minimize dust. Material may be flushed with water. Collect wash water for approved disposal.
Waste Disposal Methods:	Dispose of in accordance with federal, state and local regulations.

#### Section VIII. Special Protection Information

Eye Protection:	Goggles
Glove Requirements:	Rubber, PVC, Neoprene
Respiratory Protection:	NIOSH/MSHA approved for protection against silica and nuisance dust.
Ventilation:	Local exhaust - maintain below TLV/PEL.
Clothing:	Rubber boots, arm sleeves and apron when necessary to prevent skin contact.
Wash Requirements:	Soap and water

#### Section IX. Handling & Storage Precautions

Storage:	Keep dry.
Storage Temperature:	NA
Other Precautions:	Take necessary steps to avoid nuisance dusts.



fast-setting concrete (cont.)

<b>Section X. Shipping Information</b>
--

<b>DOT Shipping Name:</b>	<b>Bagged Portland Cement</b>
<b>DOT Hazard Class:</b>	<b>Non-hazardous – Class 50</b>
<b>DOT Reportable Quantity:</b>	<b>NA</b>

<b>Section XI. Other</b>
--------------------------

**Note: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.**