



packaging

pro atlas grout



Material Safety Data Sheet

Health = 1

Flammability = 0

Reactivity = 0

ASH GROVE PACKAGING GROUP
10809 Executive Center Drive, Ste. 321
Little Rock, AR 72211
Phone: (888) 289.1117
Fax: (501) 224.3882
www.ashgrovepkg.com

Section I. Product Identification

Trade Name: Ash Grove Pro® Atlas Grout
Synonyms: Portland Cement Mortar
Manufacturer and/or Supplier: Materials Packaging Company
Address: 10809 Executive Center Drive
Manufacturer and Emergency Telephone: (888) 289-1117
Effective Date: October 6, 2009

Section II. Hazardous Ingredients

Description	CAS#	TLV	PEL	Vapor Pres.
Portland Cement	65997-15-1	10mg/m3	15mg/m3	NA
Crystalline Silica	14408-60-7	.05mg/m3	.05mg/m3	NA
Calcium Aluminate	65997-16-2	10mg/m3	15mg/m3	NA
Calcium Sulfate	10101-41-4	10mg/m3	15mg/m3	NA
Proprietary Additives	Non-Hazardous	5mg/m3	5mg/m3	NA

Section III. Physical Data

Boiling Point:	NA	Specific Gravity (Water = 1):	NE
Vapor Pressure (mmHg):	NA	% Volatile by Volume (%):	NA
Vapor Density (Air = 1):	NA	Evaporation Rate:	NA
Solubility in Water:	Slight		
Appearance/Odor:	Light gray sanded powder; No odor		



packaging

pro atlas grout (cont.)

Section IV. Fire & Explosion Hazard Data

Flash Point:	NA
Flammable Limits – UEL (%)	NA
– LEL (%):	NA
Extinguishing Media:	NA
Special Firefighting:	Water causes product to set hard.
Unusual Fire and Explosion Hazards:	None

Section V. Health Hazard Data

Threshold Limit Value:	Respirable Dust - TLV 10mg/m ³
Effects of Overexposure:	Excessive exposure by inhalation over an extended period of time may result in the development of pulmonary diseases including pneumoconiosis and silicosis. Skin and eye irritant. Can cause alkali burns and dermatitis.
Emergency First Aid:	
Skin:	Wash thoroughly with soap and water.
Eyes:	Flush thoroughly for 15 minutes. Consult physician if irritation persists.
Inhalation:	Remove from exposure. If not breathing, give artificial respiration. Give oxygen for breathing difficulties. Consult physician.
Ingestion:	Dilute with large doses of water.

Section VI. Reactivity Data

Stability:	Stable
Stability Conditions to Avoid:	NA
Materials to Avoid:	Strong acids may cause violent, exothermic reaction.
Hazardous Decomposition Products:	NA
Hazardous Polymerization:	Will not occur

Section VII. Spill or Leak Procedures

Spill or Leak Procedures:	Use personal protective equipment to prevent dust exposures and protect against alkali burns or irritation.
Waste Disposal Methods:	Dispose of in accordance with federal, state and local regulations.

Section VIII. Special Protection Information

Eye Protection:	Goggles
Glove Requirements:	Rubber, PVC, Neoprene
Respiratory Protection:	NIOSH/MSHS approved for protection against silica and nuisance dusts.
Ventilation:	Local exhaust – maintain below TLV/PEL.
Clothing:	Rubber boots, arm sleeves and aprons when necessary to prevent skin contact.
Wash Requirements:	Soap and water

Section IX. Handling & Storage Precautions

Storage:	Store in manner to prevent contact with strong acids. Avoid contact with water to preserve product.
Storage Temperature:	Avoid freezing temperatures to insure product potential.
Other Precautions:	None



pro atlas grout (cont.)

Section X. Shipping Information
--

DOT Shipping Name:	Bagged Portland cement
DOT Hazard Class:	NA
DOT Reportable Quantity:	NA

Section XI. Other

Note: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.