



# packaging blacktop patch

## 1. Product Name

ASH GROVE® Blacktop Patch  
Product Number: 385

## 2. Manufacturer

ASH GROVE PACKAGING GROUP  
10816 Executive Center Drive, Ste. 100  
Little Rock, AR 72211  
Phone: (888) 289.1117  
Fax: (501) 224.3882  
[www.ashgrovepkg.com](http://www.ashgrovepkg.com)

## 3. Product Description

ASH GROVE® Blacktop Patch is an easy, ready-to-use asphalt mix designed and manufactured for patching and repairing potholes, cracks and seams in blacktop driveways, walks and parking lots. No mixing, heating or preparation – just pour into hole or crack and compact with a tamp or plate compactor to form a firm and durable patch.

### BASIC USE:

Recommended for repairing blacktop surfaces of:

- Driveways
- Walkways
- Parking Lots
- Cracks
- Potholes
- Loading Areas

### COMPOSITION & MATERIALS:

ASH GROVE® Blacktop Patch is an asphalt mixture formulated for repair of blacktop surfaces.

## 4. Advantages/Benefits

ASH GROVE® Blacktop Patch has several advantages including:

- No mixing required
- All-weather formula enables repairs in any weather condition – rain, cold, snow, dry, humidity or heat
- Open to traffic immediately after thorough compaction
- Reduces downtime with rapid repairs

## 5. Preparation

All surfaces that will be in contact with ASH GROVE® Blacktop Patch must be entirely free from grease, oil, paint, dirt, dust, loose materials, unsound concrete, or any other foreign substances which may interfere with the bond of the material. Slick or sealed surfaces must be thoroughly roughened.

Prior to application, chisel any loose blacktop from the opening so that all sides of the hole or crack are square to allow for proper bonding of the patch.



## 6. Mixing Instructions

ASH GROVE® Blacktop Patch is pre-blended; thus, no mixing is required before use.

## 7. Placement

Pour the ASH GROVE® Blacktop Patch into the hole or crack under repair. Fill the opening and spread Blacktop Patch to a level of about one inch higher than the surrounding surface area. Compact the patch to a level surface with a tamper or a piece of plywood may be laid over the patch and driven over with a car wheel.

## 8. Curing

No special curing is required. Traffic may begin immediately after thorough leveling and compaction.

Under certain conditions, the surface may remain tacky for a short period of time. If this occurs, spreading a light layer of sand or portland cement may be helpful.

Do not apply driveway sealer to the patched area for 60 to 90 days.

## 9. Limitations

Compaction of the patch is critical. The more compaction, the better the patch.

Prior to application, it is important to square the vertical edges of the hole.

Do not apply driveway sealer to the patched area for 60 to 90 days.

## 10. Coverage

One 60 lb. bag will yield approximately 0.38 cu. ft. when properly compacted and will cover an area of approximately 4.8 sq. ft. at a thickness of 1".

0.38 cu. ft.      60 lb. bag (27.22 kg)

## 11. Warning

ASH GROVE® Blacktop Patch contains petroleum asphalt. Normal safety wear such as protective clothing, boots, rubber gloves, dust masks, eye safety glasses should be worn while handling cement-based products. Material Safety Data Sheets are available upon request or at [www.ashgrovepkg.com](http://www.ashgrovepkg.com).

## 12. Limited Warranty

Packager, having no control over the use of the material, does not guarantee finished work. Replacement of any defective product or refund of the purchase price of defective product shall be the buyer's sole remedy under this warranty.



## blacktop patch (cont.)

THIS LIMITED WARRANTY EXCLUDES ANY LIABILITY FOR ANY CONSEQUENTIAL, INCIDENTAL, INDIRECT OR SPECIAL DAMAGES.

EXCEPT FOR THE LIMITED WARRANTY MADE ABOVE, PACKAGER SPECIFICALLY DISCLAIMS AND EXCLUDES ANY OTHER EXPRESS WARRANTY, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF GOODS AND ANY IMPLIED WARRANTY OF FITNESS OF GOODS FOR ANY PARTICULAR PURPOSE.