



## packaging concrete crack seal

### 1. Product Name

ASH GROVE® Concrete Crack Seal  
Product Number: 416

### 2. Manufacturer

ASH GROVE PACKAGING GROUP  
10816 Executive Center Drive, Ste. 100  
Little Rock, AR 72211  
Phone: (888) 289.1117  
Fax: (501) 224.3882  
[www.ashgrovepkg.com](http://www.ashgrovepkg.com)

### 3. Product Description

ASH GROVE® Concrete Crack Seal is a weather-resistant, latex crack filler designed to repair small cracks, holes and fractures in horizontal concrete surfaces. Excellent adhesion, outdoor durability and weather resistance to protect against costly water and ice damage.

#### BASIC USE:

Recommended for repairing cracks in concrete, masonry, and stucco:

- Driveways
- Patios
- Sidewalks
- Garages
- Warehouse Floors

#### COMPOSITION & MATERIALS:

ASH GROVE® Concrete Crack Seal is a high solid, ready-to-use polymerized material formulated to fill and seal cracks. This product is pourable and comes in a convenient hand-held squeezable bottle.

### 4. Advantages/Benefits

ASH GROVE® Concrete Crack Seal has several advantages including:

- Ready to use – requires no mixing, smoothing or troweling
- Applicable for interior or exterior use
- Pourable and self-leveling
- Dries to touch in 30 minutes to a gray concrete color
- Excellent adhesion, will not crack or crumble
- Strong, weather-resistant seal
- Remains flexible for continued protection

### 5. Preparation

Remove all broken and loose concrete from the crack to be repaired to ensure strong bond with the material. Rigorously and thoroughly clean surface area with hot water and a stiff brush to remove grease, oil, paint, dust and any other foreign materials, leaving the surface saturated but free of standing water. Use a pressure washer to clean the surface, for best results.



### 6. Placement

Shake bottle of ASH GROVE® Concrete Crack Seal well before using. Cut tip at an angle, allowing a ¼" to 3/8" opening. Simply squeeze ASH GROVE® Concrete Crack Seal into cracks up to ½" thick and ½" deep. For cracks over ¼" thick, apply in layers of two or more beads. Allow each layer to dry for 24 hours between applications.

### 7. Curing

Clean excess ASH GROVE® Concrete Crack Seal from the repair area with a damp cloth. Caulk can be tooled to even out the surface.

For optimum performance, apply in dry weather above 40°F. Do not apply if rain is expected within 24 hours.

### 8. Limitations

ASH GROVE® Concrete Crack Seal is not recommended for repair of large cracks (more than ½" thick and deeper than ½").

Do not place if temperatures are expected to fall below 40°F within the next 24-hour period. Protect from freezing.

### 9. Coverage

One 1 qt. bottle fills approximately 35 linear feet.

### 10. Warning

Do not take internally. If accidentally ingested, seek immediate medical attention; do not induce vomiting and do not use syrup of ipecac. Normal safety wear such as protective clothing, boots, rubber gloves, dust masks, eye safety glasses should be worn while handling cement-based products. Material Safety Data Sheets are available upon request or at [www.ashgrovepkg.com](http://www.ashgrovepkg.com).

### 11. Limited Warranty

Packager, having no control over the use of the material, does not guarantee finished work. Replacement of any defective product or refund of the purchase price of defective product shall be the buyer's sole remedy under this warranty.

THIS LIMITED WARRANTY EXCLUDES ANY LIABILITY FOR ANY CONSEQUENTIAL, INCIDENTAL, INDIRECT OR SPECIAL DAMAGES.

EXCEPT FOR THE LIMITED WARRANTY MADE ABOVE, PACKAGER SPECIFICALLY DISCLAIMS AND EXCLUDES ANY OTHER EXPRESS WARRANTY, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF GOODS AND ANY IMPLIED WARRANTY OF FITNESS OF GOODS FOR ANY PARTICULAR PURPOSE.