



packaging

mortar repair caulk



1. Product Name

ASH GROVE® Mortar Repair Caulk
Product Number: 415

2. Manufacturer

ASH GROVE PACKAGING GROUP
10816 Executive Center Drive, Ste. 100
Little Rock, AR 72211
Phone: (888) 289.1117
Fax: (501) 224.3882
www.ashgrovepkg.com

3. Product Description

ASH GROVE® Mortar Repair Caulk is specifically designed for repairing, tuckpointing and sealing cracks and joints in mortar. Apply with standard caulking gun to create a strong, durable and flexible repair to mortar joints in brick, block, stone or tile up to 3/8" thick. Non-shrinking, with excellent adhesive strength and water resistance to provide superior protection. Also may be used for sealing around windows and doors.

BASIC USE:

Recommended for repairing and sealing cracks and mortar joints in:

- Brick
- Block
- Stone
- Cinder Block
- Stucco
- Concrete

COMPOSITION & MATERIALS:

ASH GROVE® Mortar Repair Caulk is a premixed, ready to use latex caulk.

4. Advantages/Benefits

ASH GROVE® Mortar Repair Caulk has several advantages including:

- Excellent adhesion, will not crack or crumble
- Forms a strong, weather resistant seal
- Remains flexible for added durability
- Dries to a textured gray finish
- Can be painted to match wall color
- Use for interior or exterior applications

5. Preparation

Remove all broken and loose concrete from the crack to be repaired to ensure strong bond with the material. Rigorously and thoroughly clean surface area with hot water and a stiff brush to remove grease, oil, paint, dust and any other foreign materials, leaving the surface saturated but free of standing water. For best results, use a pressure washer to clean the surface.

6. Placement

Cut tip at an angle, allowing a 1/4" to 3/8" opening. Insert nail or wire through tip to puncture the inner seal of the tube. Insert tube in a standard caulk gun. Force a bead of ASH GROVE® Mortar Repair Caulk into cracks up to 3/8" thick and 3/8" deep. For cracks over 1/4" thick, apply in layers of two or more beads. Allow each layer to dry for approximately 30 minutes between applications.

7. Curing

Clean excess ASH GROVE® Mortar Repair Caulk from the repair area with a damp cloth. Caulk can be tooled to even out the surface. Wait at least 24 hours before painting over the caulk using latex paint only.

For optimum performance, apply in dry weather above 40°F. Do not apply if rain is expected within 24 hours.

9. Limitations

ASH GROVE® Mortar Repair Caulk is not recommended for repair of large cracks (more than 3/8" thick and deeper than 3/8").

Do not place if temperatures are expected to fall below 40°F within the next 24-hour period.

Only latex paint should be used when painting caulk to match wall color.

10. Coverage

Coverage will vary by the thickness of applications. One 10 oz. tube yields approximately 12 to 18 linear feet at 3/8" bead.

11. Warning

Do not take internally. If accidentally ingested, seek immediate medical attention. Normal safety wear such as protective clothing, boots, rubber gloves, dust masks, eye safety glasses should be worn while handling cement-based products. Material Safety Data Sheets are available upon request or at www.ashgrovepkg.com.

12. Limited Warranty

Packager, having no control over the use of the material, does not guarantee finished work. Replacement of any defective product or refund of the purchase price of defective product shall be the buyer's sole remedy under this warranty.

THIS LIMITED WARRANTY EXCLUDES ANY LIABILITY FOR ANY CONSEQUENTIAL, INCIDENTAL, INDIRECT OR SPECIAL DAMAGES.



mortar repair caulk (cont.)

EXCEPT FOR THE LIMITED WARRANTY MADE ABOVE, PACKAGER SPECIFICALLY DISCLAIMS AND EXCLUDES ANY OTHER EXPRESS WARRANTY, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF GOODS AND ANY IMPLIED WARRANTY OF FITNESS OF GOODS FOR ANY PARTICULAR PURPOSE.