

# Non Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 04/15/2014

Revision date: 01/21/2015

Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Non-Shrink Grout  
Utility Grout Black  
Utility Grout Grey  
Utility Construction Grout White  
Atlas Grout  
Multi Purpose Grout Grey  
Precision Grout Concentrate  
Precision Grout Grey

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Construction and repair materials.

#### 1.3. Details of the supplier of the safety data sheet

Precision Packaging Inc. or Materials Packaging Corporation  
10809 Executive Center Drive, Ste. 321  
Little Rock, AR 72211  
T 501-224-3882

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Acute toxicity 4 (Oral)  
Skin corrosion 1A  
Serious Eye Damage 1  
Skin Sensitization 1  
Carcinogenicity 1A  
Specific Target Organ Toxicity After Single Exposure 3  
Specific Target Organ Toxicity After Repeated Exposure 1

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US)



GHS05

GHS07

GHS08

Signal word (GHS-US)

Danger

Hazard statements (GHS-US)

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.

Prevention statements (GHS-US)

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dusts. Wear protective gloves and clothing as well as eye and face protection. Launder contaminated work clothing before reuse. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.

Response statements (GHS-US)

If exposed or concerned: Get medical advice/attention. If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor.

Storage statements (GHS-US)

Store to prevent dust generation. Store to keep dry until use.

Disposal statements (GHS-US)

Dispose of contents and container in accordance with all local, state and federal regulations.

Supplemental Information

Read and Follow all precautions listed in the Safety Data Sheet available on request or at [Ashgrovepkg.com](http://Ashgrovepkg.com). Additional information on the selection and use of respirators can be found in the [NIOSH Respirator Selection Logic](#) (DHHS [NIOSH] Publication No. 2005-100) and the [NIOSH Guide to Industrial Respiratory Protection](#) (DHHS [NIOSH] Publication No. 87-116) available at <http://www.cdc.gov/niosh/docs/87-116/>.

# Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

This product contains greater than 0.1% crystalline silica. Crystalline silica has been linked to cancer, silicosis, and other lung problems in conditions of prolonged airborne over-exposure.

Keep product dry until use. Avoid contact with bleed water from wet product. Clothing saturated with wet product can result in delayed, serious alkali skin burns.

### 2.3. Other hazards

Other hazards not contributing to the classification : Not applicable.

### 2.4. Unknown acute toxicity (GHS-US)

*Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White: 64 % of the mixture consists of ingredient(s) of unknown acute toxicity.*

*Atlas Grout: 58 % of the mixture consists of ingredient(s) of unknown acute toxicity.*

*MultiPurpose Grout Grey: 55 % of the mixture consists of ingredient(s) of unknown acute toxicity.*

*Precision Grout Concentrate: 48 % of the mixture consists of ingredient(s) of unknown acute toxicity.*

*Precision Grout Grey: 44 % of the mixture consists of ingredient(s) of unknown acute toxicity.*

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Calcium Sulfoaluminate Cement	(CAS No) 960375-09-1	5 - 80	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Quartz	(CAS No) 14808-60-7	7 - 60	Acute Tox. 4 (Oral), H302 Carc. 1A, H350 STOT RE 1, H372
Cement, portland, chemicals	(CAS No) 65997-15-1	5 - 50 <sup>1</sup>	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Calcium sulfate	(CAS No) 7778-18-9	2 - 45	Not classified
Cement, alumina, chemicals	(CAS No) 65997-16-2	0.5 - 30 <sup>1</sup>	Skin Irrit. 2, H315 Eye Dam. 1, H318
Gypsum (Ca(SO <sub>4</sub> ).2H <sub>2</sub> O)	(CAS No) 13397-24-5	2 - 9 <sup>1</sup>	Not classified
Ashes, residues	(CAS No) 68131-74-8	3 - 7 <sup>1</sup>	Not classified
Magnesium oxide (MgO)	(CAS No) 1309-48-4	0.1 - 4 <sup>1</sup>	Not classified
Limestone	(CAS No) 1317-65-3	0.1 - 3	Not classified
Calcium oxide	(CAS No) 1305-78-8	0.1 - 2 <sup>1</sup>	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Carbon black	(CAS No) 1333-86-4	0.5 - 1.5	Carc. 2, H351
Flue dust, portland cement	(CAS No) 68475-76-3	0.1 - 1.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Calcium Carbonate	(CAS No) 471-34-1	≤1.5 <sup>1</sup>	Not classified
Lithium carbonate	(CAS No) 554-13-2	< 0.1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 1B, H360 STOT SE 3, H335 STOT RE 1, H372
Cellulose, ethyl 2-hydroxyethyl ether	(CAS No) 9004-58-4	< 0.1	Not classified
Formaldehyde	(CAS No) 50-00-0	< 0.1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 Carc. 1A, H350 STOT SE 3, H335
Vinyl acetate	(CAS No) 108-05-4	< 0.1	Carc. 2, H351

<sup>1</sup> Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Grey

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.

# Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing. Wash contaminated clothing before reuse. Get immediate medical advice/attention.
- First-aid measures after eye contact : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : Causes severe skin burns. Symptoms may include redness, pain, blisters. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. May cause sensitisation by skin contact.
- Symptoms/injuries after eye contact : Causes serious eye damage. May cause burns. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/injuries after ingestion : Harmful if swallowed. May cause stomach distress, nausea or vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Treat for surrounding material.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Product does not burn; however its packaging may. Products of combustion may include, and are not limited to: oxides of carbon.

### 5.3. Advice for firefighters

- Firefighting instructions : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Avoid contact with skin and eyes.

### 6.2. Methods and material for containment and cleaning up

- For containment : Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Vacuum or sweep material and place in a disposal container. Provide ventilation.

### 6.3. Reference to other sections

No additional information available.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Avoid generating and breathing dust. Do not swallow. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Store to keep product dry until use. Store to prevent dust generation. Do not store in an area equipped with emergency water sprinklers. Clean up spilled material promptly.

### 7.3. Specific end use(s)

No additional information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Calcium Sulfoaluminate Cement (960375-09-1)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (respirable fraction)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)

# Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

<b>Quartz (14808-60-7)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	(30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA, (total dust) (250)/(%SiO <sub>2</sub> + 5) mppcf TWA, (respirable fraction) (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA, (respirable fraction)
<b>Cement, portland, chemicals (65997-15-1)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (respirable fraction)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)
<b>Calcium sulfate (7778-18-9)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)
<b>Gypsum (Ca(SO<sub>4</sub>).2H<sub>2</sub>O) (13397-24-5)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)
<b>Ashes, residues (68131-74-8)</b>		
USA ACGIH	ACGIH TLV (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (as inhalable fraction, PNOS) 3 mg/m <sup>3</sup> (as respirable fraction, PNOS)
USA OSHA	OSHA PEL (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (as total dust, PNOR) 5 mg/m <sup>3</sup> (as respirable fraction, PNOR)
<b>Magnesium oxide (MgO) (1309-48-4)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> TWA
<b>Limestone (1317-65-3)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)
<b>Calcium oxide (1305-78-8)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
<b>Carbon black (1333-86-4)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
<b>Flue dust, portland cement (CAS 68475-76-3)</b>		
USA ACGIH	ACGIH TLV (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (as inhalable fraction, PNOS) 3 mg/m <sup>3</sup> (as respirable fraction, PNOS)
USA OSHA	OSHA PEL (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (as total dust, PNOR) 5 mg/m <sup>3</sup> (as respirable fraction, PNOR)
<b>Calcium Carbonate (471-34-1)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable fraction)
<b>Vinyl acetate (108-05-4)</b>		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
<b>Formaldehyde (50-00-0)</b>		
USA ACGIH	ACGIH Ceiling (ppm)	0.3 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)

### 8.2. Exposure controls

Appropriate engineering controls

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

# Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Hand protection	: Wear suitable gloves.
Eye protection	: Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).
Skin and body protection	: Wear suitable clothing common to do-it-yourself projects.
Respiratory protection	: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Handle according to established industrial hygiene and safety practices.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Sanded Powder.
Colour	: Gray to Black.
Odour	: No odour.
Odour threshold	: No data available.
pH	: 10 - 12 (Highly alkaline when wet.)
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: Not applicable
Flash point	: Not applicable
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: 2.8 - 3.0
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

### 9.2. Other information

VOC content	: No data available.
-------------	----------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use. An alkali reaction from components of portland cement will corrode aluminum.

### 10.2. Chemical stability

Stable under normal storage conditions. Keep dry in storage.

### 10.3. Possibility of hazardous reactions

Strong acids may cause violent, exothermic reaction, evolve toxic gases.

### 10.4. Conditions to avoid

Moisture – product must be kept dry until ready to use.

### 10.5. Incompatible materials

Strong acids.

### 10.6. Hazardous decomposition products

None known.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

# Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Acute toxicity : Harmful if swallowed.

### Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

LD50 oral rat	627 - 1821 mg/kg
LD50 dermal rabbit	>2000 mg/kg
LC50 inhalation rat	>5 mg/l/4h

### Quartz (14808-60-7)

LD50 oral rat	500 mg/kg
---------------	-----------

### Calcium sulfate (7778-18-9)

LD50 oral rat	> 3000 mg/kg
---------------	--------------

### Ashes, residues (68131-74-8)

LD50 oral rat	> 2000 mg/kg
---------------	--------------

### Limestone (1317-65-3)

LD50 oral rat	6450 mg/kg
---------------	------------

### Carbon black (1333-86-4)

LD50 oral rat	6450 mg/kg
LD50 dermal rabbit	>3000 mg/kg

### Calcium oxide (1305-78-8)

LD50 oral rat	> 15400 mg/kg, rat
---------------	--------------------

### Flue dust, portland cement (68475-76-3)

LD50 oral rat	>1848 mg/kg, rat
---------------	------------------

### Calcium Carbonate (471-34-1)

LD50 oral rat	6450 mg/kg
---------------	------------

### Lithium carbonate (554-13-2)

LC50 inhalation rat (mg/l)	> 2.17 mg/l/4h
----------------------------	----------------

### Formaldehyde (50-00-0)

LD50 oral rat	500 mg/kg
LD50 dermal rabbit	270 mg/kg
LC50 inhalation rat (mg/l)	0.578 mg/l/4h

### Vinyl acetate (108-05-4)

LD50 oral rat	2920 mg/kg
LD50 dermal rabbit	2320 mg/kg
LC50 inhalation rat (mg/l)	11400 mg/m <sup>3</sup> 4h

Skin corrosion/irritation : Causes severe skin burns.  
 Serious eye damage/irritation : Causes serious eye damage.  
 Respiratory or skin sensitisation : May cause an allergic skin reaction.  
 Germ cell mutagenicity : Based on available data, the classification criteria are not met.  
 Carcinogenicity : May cause cancer.

### Quartz (14808-60-7)

IARC group	1
National Toxicity Program (NTP) Status	2

### Carbon black (1333-86-4)

IARC group	2B
------------	----

### Vinyl acetate (108-05-4)

IARC group	2B
------------	----

### Formaldehyde (50-00-0)

IARC group	1
National Toxicity Program (NTP) Status	2
	In OSHA Specifically Regulated Carcinogen list

Reproductive toxicity : Based on available data, the classification criteria are not met.  
 Specific target organ toxicity (single exposure) : May cause respiratory irritation.

# Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Specific target organ toxicity (repeated exposure)	: Causes damage to lungs through prolonged or repeated exposure. (Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.)
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes severe skin burns. Symptoms may include redness, pain, blisters. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. May cause sensitisation by skin contact.
Symptoms/injuries after eye contact	: Causes serious eye damage. May cause burns. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: Harmful if swallowed. May cause stomach distress, nausea or vomiting.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: No ecological consideration when used according to directions. Do not flush to sewer or allow to enter waterways.
-------------------	---

### 12.2. Persistence and degradability

**Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey**

Persistence and degradability	No data available.
-------------------------------	--------------------

### 12.3. Bioaccumulative potential

**Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey**

Bioaccumulative potential	No data available.
---------------------------	--------------------

### 12.4. Mobility in soil

**Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey**

Ecology - soil	No data available.
----------------	--------------------

### 12.5. Other adverse effects

Other adverse effects	: No data available.
-----------------------	----------------------

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.
--------------------------------	---

## SECTION 14: Transport information

In accordance with DOT:

### 14.1. UN number

Not applicable.

### 14.2. UN proper shipping name

Not applicable.

### 14.3. Additional information

Other information	: No supplementary information available.
-------------------	---

# Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Cement, portland, chemicals (65997-15-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Calcium sulfate (7778-18-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Cement, alumina, chemicals (65997-16-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Ashes, residues (68131-74-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Magnesium oxide (MgO) (1309-48-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Calcium oxide (1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Flue dust, portland cement (68475-76-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Calcium Carbonate (471-34-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Lithium carbonate (554-13-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

##### Cellulose, ethyl 2-hydroxyethyl ether (9004-58-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Formaldehyde (50-00-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 302 (Specific toxic chemical listings)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 302 Threshold Planning Quantity (TPQ)	500
--	-----

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

##### Vinyl acetate (108-05-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 302 (Specific toxic chemical listings)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 302 Threshold Planning Quantity (TPQ)	1000
--	------

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

#### 15.3. US State regulations

##### Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

State or local regulations	This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	--



# Non-Shrink Grout; Utility Grout Black; Utility Grout Grey; Utility Construction Grout White; Atlas Grout; Multi Purpose Grout Grey; Precision Grout Concentrate; Precision Grout Grey

## Safety Data Sheet


according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

IARC (I)	International Agency for Research on Cancer.
	1 - Carcinogenic to humans; 2A - Probably carcinogenic to humans; 2B - Possibly carcinogenic to humans; 3 - Not classifiable; 4 - Probably not carcinogenic to humans.
NTP (N)	National Toxicology Program.
	1 - Evidence of Carcinogenicity; 2 - Known Human Carcinogens; 3 - Reasonably anticipated to be Human Carcinogen; 4 - Substances delisted from report on Carcinogens; 5 - Twelfth Report - Items under consideration.

### SECTION 16: Other information

Date of issue	:	04/15/2014
Revision date	:	01/21/2015
Version	:	1.1
Data sources	:	SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
NFPA health hazard	:	3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	:	0 - Materials that will not burn.
NFPA reactivity	:	0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*