



packaging paver sand



1. Product Name

ASH GROVE® Paver Sand
Product Number: 291

2. Manufacturer

ASH GROVE PACKAGING GROUP
10809 Executive Center Drive, Ste. 321
Little Rock, AR 72211
Phone: (888) 289.1117
Fax: (501) 224.3882
www.ashgrovepkg.com

3. Product Description

ASH GROVE® Paver Sand is coarse, granular sand specifically designed to work as a bedding layer and joint sand for paver applications. Firmly locks and binds all types of pavers together, including flagstone, brick, block and interlocking pavers, in a friction joint without using mortar or concrete. Perfect for building driveways, patios, walkways and entryways. It forms solid paver joints that resists water penetration and does not wash out easily.

BASIC USE:

Recommended for:

- Patios
- Driveways
- Walkways
- Sidewalks
- Gardens
- Entryways

COMPOSITION & MATERIALS:

ASH GROVE® Paver Sand is coarse, granular sand.

4. Advantages/Benefits

ASH GROVE® Paver Sand has several advantages including:

- Ready to use
- Convenient bag size
- Best results when used with ASH GROVE® Paver Base
- Backed by Quality Controlled Testing

5. Preparation

ASH GROVE® Paver Base and ASH GROVE® Paver Sand are designed to work together to form a firm foundation for all kinds of paver styles and projects. Whether you choose brick, stone, or slate pavers to use in patio, walkway, or driveway, a better base can be built with the one-two combination of ASH GROVE® Paver Base and ASH GROVE® Paver Sand.

ASH GROVE® Paver Base forms a base layer of variable size stones, providing superior drainage and stability. ASH GROVE® Paver Sand works as both a bedding layer and

joint sand to hold pavers securely in place. Follow these simple step-by-step instructions to form a long-lasting firm foundation.

DESIGN: Choose from a wide variety of sizes, shapes, and colors available for your paver design. Be sure to use strong, high-quality pavers that will not crack under intended use.

EXCAVATE: Excavate the area to be paved with a shovel or skid loader, according to the paver manufacturer's instructions. Typically, the area should be deep enough to allow for a 4" PAVES BASE, a 1" PAVES SAND bedding layer, and the paver depth. Compact the soil with a hand tamper, roller, or mechanical compactor.

6. Placement

BASE: Overlay the ground with a weed blocker fabric to prevent weed growth. Fill with 2 - 4" of PAVES BASE and level with a 2 x 4 screed board. Compact the base layer with a hand tamper, roller, or mechanical compactor.

BEDDING: After installing the paver edging, pour PAVES SAND to form a 1" bedding layer over the PAVES BASE. Use a screed board to level the sand. Compact the bedding layer with a hand tamper, roller, or mechanical compactor.

PAVERS: Install the pavers according to the manufacturer's specifications. Use a rubber mallet to position and level the pavers.

7. Curing

SWEEP: Spread PAVES SAND over the surface of the pavers and sweep it into the joints until all joints are full of sand. Reapply PAVES SAND to fill the joints as needed over the next couple of weeks.

6. Coverage

One 50 lb. bag (22.68 kg) yields approximately 0.5 cu. ft. of sand or will fill an area approximately 6 sq. ft. x 1 in. (25 mm) deep.

7. Warning

ASH GROVE® Paver Sand contains sand. Avoid breathing dust from this product, which contains crystalline silica, which has been linked to lung diseases and cancer. Use a NIOSH approved dust respirator and use only with adequate ventilation to keep dust levels below permissible levels. Normal safety wear such as protective clothing, boots, rubber gloves, dust masks, eye safety glasses should be worn while handling the product. Material Safety Data Sheets are available upon request or at www.ashgrovepkg.com.



paver sand (cont.)

8. Limited Warranty

Packager, having no control over the use of the material, does not guarantee finished work. Replacement of any defective product or refund of the purchase price of defective product shall be the buyer's sole remedy under this warranty.

THIS LIMITED WARRANTY EXCLUDES ANY LIABILITY FOR ANY CONSEQUENTIAL, INCIDENTAL, INDIRECT OR SPECIAL DAMAGES.

EXCEPT FOR THE LIMITED WARRANTY MADE ABOVE, PACKAGER SPECIFICALLY DISCLAIMS AND EXCLUDES ANY OTHER EXPRESS WARRANTY, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF GOODS AND ANY IMPLIED WARRANTY OF FITNESS OF GOODS FOR ANY PARTICULAR PURPOSE.

Ash Grove Packaging reserves the right to change specifications without notice.